



INCA WALL EN


INCA WALL

PANADERO


MEASURES / MÅTT / MITAT / MÕÖDUD / MÅL



129/114 kg



290x360 mm



150-153 mm

CHARACTERISTICS / EGENSKAPER / OMINAISUUDET / ISELOOMUSTUSED / EGENSKABER



7,6 KW



80,7 %



0,12 %



800 °C



750 °C

EAN 8426964185089
REF. PANADERO 18508



EXTERNAL AIR INTAKE / EXTERNE TILLUFT / ILMANOTTOAUKKO / VÄLISÖHU SISEND / EKSTERN LUFTINDTAG / EKSTERN LUFTILFØRSEL **Ø80 mm**



230 m³

HEATING VOLUME / UPPVÄRMNINGSYTA / LÄMMITYSALA / KÜTMISVÖIMSUS / VARMEVOLUMEN / OPPVARMINGSVOLUM



VERMICULITE LINING / VERMIKULIT / TULISIJA PÄÄLLYSTETTY VERMIKULIITILLA / VERMIKULIITISOLATSIOON / VERMICULITE-BELÆGNING / VERMICULITE ISOLERT



CLEAN GLASS SYSTEM / SJÄLVRENGÖRANDE GLAS / ITSEPUHDISTUVA LASI / KLAASIPUHASTUSSÜSTEEM / RENT GLAS SYSTEM / RENT GLASSYSTEM



DOUBLE COMBUSTION / DUBBEL FÖRBRÄNNING / KAKSOISPOLTO / TOPELPÖLEMINE / DOBBELT FORBRÆNDING / DOBBELT KOMBUSTION



WOOD LOGS UP TO / MAXIMAL VEDLÅNGD / POLTTOPUUN PITUUS PYSTYYN / KUNI PIKKUSED KÜTTEPUUD / BRÆNDESTYKKER OP TIL / VEDKUBBER OPPTIL **40 cm**



PRINTED GLASS / TONAT GLAS / SILKKIPAINETTU LASI / SIIDITRÜKITUD KLAAS / TRYKT GLAS / TRYKT GLASS



CAST IRON GRILL / GJUTJÄRNSGALLER / VALURAUTARITILÄ / MALMREST / STØBEJERNRIST



TRIVISION / TREVISNING / KOLMIPUOLINEN TULINÄKYMÄ / KOLMEPOOLNE TULEVADE / TRE-SIDET ILDSYN / TRE-SIDIG ILDSYN

